

Falcon Evo

The Falcon Evo range has been specifically designed for the large scale contractor.

With high specification options and a range of controls to select from, the Falcon range is the first choice for contractors.

Key Features

- 5.5m, 6.0m or 6.5m reach
- Heavy Duty Linkage
- 125 l/min independent system
- 1.2m or 1.5m cutting head
- Parallel option



Want to know more about the Falcon Evo range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: [www.bomford-turner.com/
landscape/arm-mowers/falcon-evo/](http://www.bomford-turner.com/landscape/arm-mowers/falcon-evo/)





Pressed steel first arm construction

Strength and weight-saving without compromise.



Oil cooler

Standard on all models
(cable controls as an option).



125L and 72 HP pumps

Comes as standard, with 137L and 85HP options.

Product Specification

● Standard ○ Optional — Not Available


Falcon Evo	5.5m (18'1")	6.0m T (19'8")	6.5m T (21'4")	Bi-Way 5.5 (18'1")
Tractor requirements				
Minimum horse power	75hp	75hp	75hp	75hp
Minimum weight	3500kg 7716lbs	3800kg 8378lbs	4250kg 9367lbs	3000kg 6614lbs
Base unit mounting options				
Front mount	—	—	—	○
Mid-mount	—	—	—	—
Rear mount	●	●	●	●
Three point linkage (CAT II)	●	●	—	●
Axle bracket	○	○	●	○
Overall machine parameters				
Machine weight with head and oil	1790kg 3946lbs	1890kg 4167lbs	2190kg 4828lbs	1930kg 4255lbs
Capacity of oil tank	250L 66USG	250L 66USG	250L 66USG	250L 66USG
Weight of machine with oil but without head	1500kg 3307lbs	1600kg 3527lbs	1900kg 4189lbs	1640kg 3616lbs
Controls				
Cable Control (CC)	●	●	●	●
Low pressure hydraulics (LPH)	○	○	○	○
Electronic proportional control (EPP)	○	○	○	○
Intelligent control system (ICS)	○	○	○	—
Cable rotor reverse	○	○	○	○
Electronic rotor reverse	○	○	○	○
Hydraulic system				
System capability	74hp	74hp	74hp	74hp
Pump flow rate	125L 33USG	125L 33USG	125L 33USG	125L 33USG
Pump type (Gear/Piston/Helical)	Gear	Gear	Gear	Gear
Pump arrangement (Twin/In-line)	Twin	Twin	Twin	Twin
Independent hydraulics	●	●	●	●
Oil cooler	○	○	○	○

Falcon Evo	5.5m (18'1")	6.0m T (19'8")	6.5m T (21'4")	Bi-Way 5.5 (18'1")
Arm features and main frame				
Forward arm	—	—	—	—
Forward arm reach	—	—	—	—
Telescopic arm	—	●	●	—
Telescopic arm stroke	—	900mm 3'	900mm 3'	—
Power slew	●	●	●	●
Power slew angle	94°	94°	94°	94°
Gravity breakout protection	—	—	—	—
Hydraulic breakout protection	●	●	●	●
Arm float - manual operation	○	○	○	○
Arm float - electronic operation	○	○	○	○
Head float - manual operation	●	●	●	●
Head float - electronic operation	○	○	○	○
Left hand cutting	○	○	○	○
Right hand cutting	○	○	○	○
Left and right hand cutting	—	—	—	—
Arm attachments available				
Variable track bracket (VTB)	○	○	○	—
Sheartrim cutter bar	○	○	○	○
Pro-Saw	○	○	○	○
Ditch cleaner	○	○	○	—
Rotary head	○	○	○	—
Accessories				
Road Lights	●	●	●	●
Debris Blower	○	○	○	○
Warning Arrow (Magnetic / Fixed)	○	○	○	○
Cab Guard Kit	●	●	●	●
Cutting heads (For Flail compatibility see page 95)				
1.2m Pro-Cut-115/150mm roller	○	○	○	○
1.5m Pro-Cut-115/150mm roller	○	○	○	○
1.2m Pro-Cut ISMP-115/150mm roller	○	○	○	○
2m HD head	○	○	○	○

Working Reach

Head used for calc's: 1.2 Pro-Cut

	Falcon 5.5m (18'1")	Falcon 6.0m T (19'8")	Falcon 6.5m (21'4")	Falcon Bi-Way 5.5m (18'1")
A	5.54m/18'2"	6.07m/19'11"	6.42m/21'1"	5.72m/18'9"
B	5.69m/18'8"	6.22m/20'5"	6.74m/22'1"	5.82m/19'1"
C	3.49m/11'5"	4.42m/14'6"	4.10m/13'11"	3.86m/12'8"
D	4.42m/14'6"	4.54m/14'11"	5.65m/18'6"	4.74m/15'7"
E	6.06m/19'	6.18m/20'3"	7.67m/25'2"	6.92m/22'8"
X	1.35m/4'5"	1.35m/4'5"	1.35m/4'5"	1.35m/4'5"
Y	1.0m/3'4"	1.0m/3'4"	1.0m/3'4"	1.0m/3'4"



Bi-Way arm options

Allows the machine to cut in both forward and reverse directions.

