

Raptor

The new Raptor verge mower is the ideal choice for users who have a dedicated shoulder mowing operation to perform.

The Raptor can be front mounted allowing the fitting of a Bomford arm mower on the rear giving a 3.5m cut, in one pass. The Raptor can effortlessly work around street furniture and varying ground levels.

Key Features

- Cutting widths of 1.2, 1.6 or 2.0m.
- Front or Rear mounted options
- Banks cutting between 90° up and 50° down
- Cat II three point linkage
- Choice of flails



Product Specification

Raptor	1200	1600	2000
Reach	2.84m / 9'4"	3.24m / 10'7"	3.64m / 12"
Cutting Width	1.2m / 4'	1.6m / 5'3"	2m / 6'6"
Max Offset	750mm / 2'6"	750mm / 2'6"	750mm / 2'6"
No. of Flails	32	44	54
PTO Speed (rpm)	1000 / 540	1000 / 540	1000 / 540
Cowl Angle Movement	140° (+90° to -50°)	140° (+90° to -50°)	140° (+90° to -50°)
Power Requirement	40hp	45hp	70hp
Weight	620kg / 1367lbs	830kg / 1830lbs	900kg / 1984lbs
Front Mountable	○	○	○



Want to know more about the Raptor range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: www.bomford-turner.com/landscape/flail-mowers-and-toppers/raptor/