



Growler Mulching Head



Tiger Growler mulching head, the newest addition to Tiger's premium line of boom mower attachments.

The Growler is designed with explosive power to tackle heavy brush and mulch 10" trees into wood chips. It will clear ditches, tree lines and road right-of-ways or other wooded areas with virtually no clean up after the job is complete.

The Tiger Growler head attaches to most existing Tiger booms, making this the perfect addition for all your mowing and clearing needs.



DURABILITY INNOVATION

COMMITMENT

Tiger Features

Rugged. Durable. Built to last...

Tiger's reputation for quality and reliability means the Growler's rugged design is built to withstand the harshest conditions and keep on mulching.

The precisely engineered, staggered tooth cutter shaft design provides the operator with a smooth running cutter head.

The precision and engineering integrated into this new head provide strength and performance for tough conditions.

Embrace the power and performance the Growler adds to your operation in clearing miles of small trees and under brush in a single day.



ROAD READY




FRONT VIEW OF MULCHING HEAD



REAR RUBBER FLAP OR REAR CHAIN GUARD



HYDRAULIC DRIVEN HEAD TILT



10" CUT



STOW POSITION



Premium features include a hydraulic tilt cylinder to rotate mulching head, allowing maximum tooth exposure. The Growler Mulching head is also equipped with a piston motor to ensure a quick recovery time and high torque when mulching hardwoods or tough to mulch trees. This piston motor is designed to provide constant torque of the cutter head when taking down a large tree or tough vegetation. This mulching head is retro-fittable to all existing Bengal boom mowers with the purchase of a few additional components and an oil return line. With field-proven performance and strength, the Growler mulching head will allow additional versatility for your roadside mowing tractor package.

Features

Cut Diameter	10" trees or heavy brush
Cutter Head	36" cutting shaft
Cutter Shaft	Dynamically balanced 12" cutter shaft
Cutter Teeth	30-Rotatable and Replaceable Quad-Cut teeth
Gathering Arms	Designed to bring additional brush and material into cutting drum for 50" total cutting area
Hydraulic Tilt Cylinder	Cylinder gives tilt to cutter head, allowing maximum tooth exposure
Shear Plate	Engineered to cut cut trees or brush into smaller pieces
Cutter Housing	3/8" Domex Steel @ 100,000 Yield Strength
Hydraulic System	Flow is 41.2 GPM with operating pressure at 3000 psi for Bengal and 3500 psi for Saber
Safety Stop	7 Second Shut Down
Weight	930 lbs.

Tiger Mowers LLC
3301 North Louise Ave.
Sioux Falls, SD, USA 57107
800.843.6849
www.tigermowers.com



Dealer Info:

An Alamo Group® Company
Specifications are subject to change. Optional equipment may be shown.

Meets All Applicable ANSI / SAE Test Standards.
© 2022 Tiger Mowers LLC. All Rights Reserved. Printed in the USA.

