


SPEARHEAD

DESTROYER FLAIL



DESTROYER FLAIL FEATURES



	TRACTOR HP	PTO SPEED	TRANSPORT WIDTH	3 POINT LINKAGE MOUNTING	CUTTING WIDTH	TOOTH TYPE	NO. OF TEETH	CUTTING HEIGHT
DESTROYER FLAIL 140F	80hp (60kW)	1000rpm	1.70m (5' 7")	✓	1.40m (4' 7")	Heavy Duty	36	15mm - 60mm (0.6" - 2.4")
DESTROYER FLAIL 160F	80hp (60kW)	1000rpm	1.92m (6' 4")	✓	1.92m (5' 3")	Heavy Duty	48	15mm - 60mm (0.6" - 2.4")
DESTROYER FLAIL 200F	80hp (60kW)	1000rpm	2.34m (7' 9")	✓	2.4m (6' 6")	Heavy Duty	60	15mm - 60mm (0.6" - 2.4")

POWER THROUGH THE ROUGHEST OF TERRAIN



HEAVY SCRUB




FORESTRY



AIRFIELD



WATERWAYS



DOUBLE CURTAIN
FRONT AND REAR CHAINS

REPLACEABLE BOLT-ON SKIDS

HEAVY DUTY ROTOR WITH HARDENED TEETH

The Destroyer Flail is designed to cut and pulverize heavy scrub and forestry regrowth up to 150mm. It is the perfect choice for maintenance of areas such as woodland rides, dense scrub and plantations.

This highly robust machine features heavy duty mulching teeth fitted on an electronically balanced rotor mounted on enclosed, self-aligning bearings. A heavy-duty driveline with 5 or 6 belts (model dependent), gives reliable power transmission in the most challenging conditions. Other key features are a hydraulic opening hood and an adjustable push frame which work together to ensure that material is channeled efficiently into the mulcher.

The Destroyer Flail is available in a choice of working widths between 1.4 and 2.0 metres and is ideal for forward and reverse drive.

SPECIFICATION	DESTROYER FLAIL 140F	DESTROYER FLAIL 160F	DESTROYER FLAIL 200F
Machine weight	985kg (2172lbs)	1055kg (2326lbs)	1240kg (2734lbs)
Hitch	Category 2 with clevis top link	Category 2 with clevis top link	Category 2 with clevis top link
Hitch position	Rear mount only	Rear mount only	Rear mount only
Cutting width	1.40m (4' 7")	1.60m (5' 3")	2.00m (6' 6")
Overall width	1.70m (5' 7")	1.92m (6' 4")	2.34m (7' 9")
Overall length	1.12m (3' 8")	1.12m (3' 8")	1.12m (3' 8")
Cutting height	15mm - 60mm (0.6" - 2.4")	15mm - 60mm (0.6" - 2.4")	15mm - 60mm (0.6" - 2.4")
Cutting capacity	150mm (5.9")	150mm (5.9")	150mm (5.9")
Recommended tractor HP	80hp (60kW)	80hp (60kW)	80hp (60kW)
Power take-off speed	1000rpm	1000rpm	1000rpm
Gearbox	Cast Iron housing with fully enclosed driveline	Cast Iron housing with fully enclosed driveline	Cast Iron housing with fully enclosed driveline
Input shaft	1" 3/8 Z6	1" 3/8 Z6	1" 3/8 Z6
Gearbox lubricant	EP80-90W or GL-4 / GL-5 oil	EP80-90W or GL-4 / GL-5 oil	EP80-90W or GL-4 / GL-5 oil
Gearbox oil capacity	4 litres (7 pints)	4 litres (7 pints)	4 litres (7 pints)
Cowl construction	All welded construction	All welded construction	All welded construction
Skid construction	Replaceable bolt-on skid	Replaceable bolt-on skid	Replaceable bolt-on skid
Teeth	Heavy-duty tooth	Heavy-duty tooth	Heavy-duty tooth
Tooth quantity	36	48	60
Tooth tip speed	53 m/s (10433 fpm)	53 m/s (10433 fpm)	53 m/s (10433 fpm)
Rotor diameter	229mm (9")	229mm (9")	229mm (9")
Number of belts	5	5	6

SPEARHEAD

📍 Station Road, Salford Priors, Evesham, Worcestershire, WR11 8SW, England ☎ +44 (0)1789 491860

✉ enquiries@spearheadmachinery.com 📧 spearheadmachinery.com 🐦 📘 SpearheadWorld

